

10.40.10.190: KIRK Wireless Server 600v3

- Configuration
- General
- IP
- ETH0
- ETH1
- LDAP
- DECT
- Administration
- DECT
- PBX
- Gateway
- Download
- Upload
- Diagnostics
- Reset

System **Master** Features Radio

admin

Mode

Protocol

Proxy

Alt-Proxy

Domain

Registrations per second

Enbloc Dialing

Send inband DTMF

Allow DTMF through RTP

Enable messaging to PBX

Idle Display Update

Disable broadcast delay

Response timeout

SIP Interop Tweaks

Registration time-to-live (expires) sec

STUN Server

Hold Signaling

Hold before Transfer

Accept INVITE's from anywhere

Name for Authentication

KPML support

LDAP Directory Search

Enable directory search

Server	<input type="text"/>	Dialing Location	
User	<input type="text"/>	Country Code	<input type="text"/>
Password	<input type="text"/>	Area Code	<input type="text"/>
Search Base	<input type="text"/>	National Prefix	<input type="text"/> (carrier specific)
Name Attributes	<input type="text"/>	International Prefix	<input type="text"/> (carrier specific)
Number Attributes	<input type="text"/>	External Line	<input type="text"/> (pbx specific)
		Subscriber Numbers	<input type="text"/> (pbx specific)

Registration for anonymous devices

Registration Name / Number /

Deactivate Master if no connection

OK

Cancel